

PBB, Inc.
 1311 E. Philadelphia St.
 Ontario, CA 91761

“THERE CAN BE ONLY ONE”



STAINLESS STEEL CONTINUOUS HINGES

PBB	HAGER	SELECT	ABH	MCKINNEY	IVES	STANLEY	MARKAR	GALLERY
CH51	790-900	SL 300	A500	MCK FM 300	700	651	FM300	951
CH52CG	~~	SL310	~~	~~	~~	~~	HG310	~~
CH51G	790-905	SL 305	A505	MCK FM 305	705	652	HG305	952
CH51L	790-915	~~	~~	MCK HG 315	~~	653	HG315	953
CH52CL	790-911	SL 310	A511	MCK HG 311	711	656	HG311	956
CH52	790-904	~~	~~	~~	~~	~~	HM304	~~
CH52L	~~	SL306	~~	~~	~~	~~	HG306	~~
CH53	~~	SL 302	A502	MCK FS 302	702	~~	FS302	957
CH53I	~~	~~	~~	~~	~~	~~	FS301	~~
CH54	790-903	SL303	A503	MCK HM 304	~~	654	HS303	954
CH5GB	~~	SL 308	~~	~~	~~	~~	HG308	~~
CH5GS	~~	SL 308	~~	~~	~~	~~	HG308	~~
CH5LB	~~	~~	A538	~~	~~	~~	EG-C-308	~~
CH5LS	~~	~~	~~	~~	~~	~~	EG-C-308	~~
CH5AB	~~	~~	~~	~~	~~	~~	EG-T-308	~~
CH5AS	~~	~~	~~	~~	~~	~~	EG-T-308	~~



Stainless Steel Continuous Hinge

QUALITY ADVANTAGE

Thicker material (.090" vs. .075") and large pin diameter provide extra strength to hold the door weight and for high frequency usage. Hinge pin is permanently locked in place by means of C-lock pin at top.

PBB continuous hinges are welded on the top and bottom knuckles to prevent the knuckle from opening under extreme operating conditions thus preventing the door to sag.

All half mortise and half surface, hinges are symmetrical. All sizes are non-handed for full mortise, full surface.

INSTALLATION ADVANTAGE

Drill a perfectly straight and centered screw hole every time automatically by using the drill tool. Reduce installation time by no longer having to find the center of the screw holes and trying to drill straight.

Use two slotted screw holes on top and two slotted screw holes on the bottom of the hinge to initially mount the hinge onto the door and frame. The door position can then be easily adjusted before installing the remaining screws to secure the final door position.

The PBB 85" continuous hinges are marked at 83" and 79" spot on the back of the hinge. The hinge can be cut with a metal cut-off saw to desired length in seconds without cutting through screws holes or hinge bearings. Stock one size and have three different sizes available for field application.

New patent pending clip and go system saves time, money and effort.

- Plated into most finishes
- Meets UL10B, UL10C, UBC 7-2
- Fire rated from 20 minutes to 3 hours



MODELS

